



AGRITEC – Flail mower GS33



Short description of GS33

AGRITEC flail mower for professional communities, service providers and other users

With the **AGRITEC** flail mowers of the GS33 series the high standards of a **clean cutting pattern**, as well as the **faster decomposition** of the cuttings are met.

The **round shape of the housing** and the **high rotor speed** ensure a **perfect material flow** without any turbulences and formation of lumps. The mowed and crushed material is deposited with **high throwing speed** over the entire working width behind the rear roller – even in case of wet grass. Thus the decomposition process is stimulated and the putrefaction is prevented.

The **large housing overhangs** in the front and the rear, as well as the additional **rubber aprons** hung on the hinges prevent the escape of stones and other objects – this way the mowing will be **secure**.

The **special** rectangular-profile rotor, which is electronically balanced at **operating speed**, is **revolutionary** in the field of mowing technology. The rotor is perfect due to its quiet running – best mowing results – stable operation.

Model	Operating width	External width	Weight	Cup knife	Y knife	Power requirement
3-point CAT.1 rear or front mounting, CAT.0 coupling triangle						
GS33-090FG	90 cm	106 cm	143 kg	20	40	12 – 45 hp
GS33-110FG	110 cm	126 cm	157 kg	24	48	17 – 45 hp
GS33-130FG	130 cm	136 cm	170 kg	28	56	22 – 45 hp
GS33-150FG	150 cm	156 cm	185 kg	32	64	24 – 45 hp



Technical features

- CAT. 1 **rear** or **front** mounting, CAT.0 coupling triangle, large-area mower
- Stable rotor made of **rectangular profile**
- Blade suspension with **stainless steel shackle**
- **Self-cleaning** rear roller
- equipped as standard with **skids**
- **Soil-conserving** sloping rear roller
- Optional with **fine mowing profile**

AGRITEC specialist dealer

WAM GmbH **AGRITEC**
Dornierstr. 10 D-68804 Altlußheim
Phone: + 49 (0) 6205 3949 0 fax +49 (0) 6205 3949 49

www.**AGRITEC**.de

