







Short description of BS400/BS450

The AGRITEC embankment mower of the BS400/BS450 series has been specifically designed for municipal and agricultural tractors that have a track width of minimum 160 cm. This makes it ideal for the mowing of embankments and hedges in the landscaping and garden maintenance, as well as for working in roadside vegetation.

It is very manoeuvrable and extremely versatile due to the high connection point of the first arm.

Due to the innovative technology and its comfortable operation, the mowing of embankments will be easy and convenient.


High quality workmanship and effective components guarantee an impressive quality of work.

The standard built-in oil cooler permanently offers you the full power of the AGRITEC embankment mower. Due to the oil cooling, our machines are generally designed for continuous load. This way the professional operation will be safe, versatile and reliable.



Model	Operating width	Extension arm	Weight arm	Power req. tractor	Tractor weight/min.	Tractor track width	Angle head	Liter	Liter/ min
BS400	105 cm	400 cm	600 kg	ab 45 PS	>1800 kg	>160 cm	200°	140	56
BS450	105 cm	450 cm	620 kg	ab 45 PS	>1800 kg	>160 cm	200°	140	56

Dimensions (cm)													
Model	Α	В	С	D	Е	F	G	Н	ı	L	М	N	0
BS400	402	190	95	110	250	470	360	295	170	181	105	160	260
BS450	452	204	54	140	216	547	409	306	197	195	125	-	276





Technical features

- · CAT.1 or CAT.2 three-point rear mounting
- · Comes standard with oil cooler
- · Designed with safety chains, tool head with floating position
- · Operation via control lever, electric control available optionally
- Mowing head: 105 cm
- · Rotor with bidirectional rotation
- Hedge trimmer/lopper optionally available (other attachments on request)

AGRITEC specialist dealer

WAM GmbH AGRITEC
Dornierstr. 10 D-68804 Altlußheim
Phone: + 49 (0) 6205 3949 0 fax +49 (0) 6205 3949 49







