



AGRITEC – Flail mower GS60



Short description of GS60

The **AGRITEC** flail mower of the GS60 series has been specifically designed to be used with tractors and carrier vehicles, as well as with compact tractors of **45-120 hp** with a PTO drive of 540 or 1000 U/min.

The **AGRITEC** flail mowers of the GS60 series are equipped as standard with a three-point linkage in the rear or the front, CAT.1 or CAT.2.

The GS60 series is equipped with a **hydraulic** side shift.

The **round shape of the housing** ensures the **optimal** and **turbulence-free** flow of materials. The **heavy** (1,600 g), **self-sharpening** pruning hammers combined with the standard built-in **fine mower profiles** provide the best possible grinding of the mulch material, thus ensuring a rapid **decomposition**.

Due to the **high throwing speed**, the mulch material is kept by the **air** behind the rear roller on the entire working width, thus the water balance of the soil is positively influenced.

Even bushy materials with strong, knotty parts of up to $D = 8 \text{ cm}$, as well as strawy plants are securely absorbed and crushed.

The rotor is made of high quality seamless drawn **precision tubular steel** and is electronically balanced at full operating speed. This ensures an **extremely smooth operation during continuous use**.

Model	Operating width	External width	Side shift	Weight	Blade	Power requirement
GS60-160V	160 cm	182 cm	46 cm	598 kg	12	45 – 80 PS
GS60-180V	180 cm	202 cm	46 cm	646 kg	16	55 – 80 PS
GS60-200V	200 cm	222 cm	55 cm	720 kg	16	80 – 115 PS
GS60-220V	220 cm	242 cm	55 cm	780 kg	18	80 – 115 PS
GS60-250V	250 cm	273 cm	55 cm	872 kg	24	90 – 120 PS



Technical features

- CAT.1 and CAT.2, 540 or 1000 U/min **front or rear mounting**
- Free-wheeling integrated in transmission
- Gearing with **through shaft** for **combined** rear and front mounting
- Stable rotor made of **precision tubular steel, electrically balanced**
- **Maintenance-free** rear roller bearing
- **Self-cleaning** rear roller
- Standard **skids** and **fine mower profile**
- Soil-conserving oblique rear roller

AGRITEC specialist dealer



WAM GmbH **AGRITEC**
Dornierstr. 10 D-68804 Altlußheim
Phone: + 49 (0) 6205 3949 0 fax +49 (0) 6205 3949 49

www.**AGRITEC**.de

