



AGRITEC – Flail mower GS70



Short description of GS70

The **AGRITEC** flail mower of the GS70 series has been specifically designed to be used with tractors and carrier vehicles, as well as with compact tractors of **90–190 hp** with a PTO drive of 540 or 1000 U/min.

The **AGRITEC** flail mowers of the GS70 series are equipped as standard with a three-point linkage in the rear or the front, CAT.2 or CAT.3.

The GS70 series is equipped with a **hydraulic** side shift.

The **round shape of the housing** ensures the **optimal** and **turbulence-free** flow of materials. The **heavy** (1,800 g), **self-sharpening** pruning hammers combined with the standard built-in **fine mower profiles** provide the best possible grinding of the mulch material, thus ensuring a rapid **decomposition**.

Due to the **high throwing speed**, the mulch material is kept by the **air** behind the rear roller on the entire working width, thus the water balance of the soil will be positively influenced.

Even bushy materials with strong, knotty parts of up to $D = 10$ cm, as well as strawy plants are securely absorbed and crushed.

The rotor is made of high quality seamless drawn **precision tubular steel** and is electronically balanced at full operating speed. This ensures an **extremely smooth operation during continuous use**.

Model	Operating width	External width	Side shift	Weight	Blade	Power requirement
GS70–280V	280 cm	299 cm	55 cm	1.550 kg	24	90 – 190 PS

The best choice for extreme conditions!



Technical features

- CAT.2 and CAT.3, 540 or 1000 U/min **front** and **rear mounting**
- Free-wheeling integrated in transmission
- Gearing with **through shaft** for **combined** rear and front mounting
- Stable rotor made of **precision tubular steel, electrically balanced**
- **Maintenance-free** rear roller bearing
- **Self-cleaning** rear roller
- Standard **skids** and **fine mower profile**
- Soil-conserving oblique rear roller

AGRITEC specialist dealer



WAM GmbH **AGRITEC**
Dornierstr. 10 D-68804 Altlußheim
Phone: + 49 (0) 6205 3949 0 fax +49 (0) 6205 3949 49

www.**AGRITEC**.de

