





Short description of AT20

The AGRITEC rotary hoe is a very important and valuable soil cultivation device in the field of gardening and landscaping.

The laterally adjustable rotary hoe of the AT20 series has been specifically developed to be used with municipal and compact tractors, as well as with agricultural carrier vehicles of 35–80 hp.

It has rigid and angled cutting blades that are arranged helically around the cutter shaft. This ensures an extremely smooth running with minimal power consumption and produces a clean cut.

The cutter shaft is powered by a maintenance-free chain in oil bath. An automatic chain adjuster ensures the optimal positioning of the chain. The rear protective cover and the integrated levelling bar, adjustable via chain, eliminates the bumps.

Due to its <u>side</u> shifting capacity, the AT20 is also particularly suitable for use in vineyards and orchards. But the AT20 rotary hoe has proven itself <u>thousands</u> of times in communal farms, tree nurseries and greenhouses as well.

Model	Operating width	External width	Side shift	Weight	Blade	Power requirement
AT20-085V	85 cm	101 cm	2 cm	123 kg	20	from 12 hp
AT20-100V	102 cm	120 cm	11 cm	134 kg	24	from 15 hp
AT20-120V	120 cm	135 cm	19 cm	144 kg	28	from 20 hp
AT20-135V	136 cm	152 cm	27 cm	155 kg	32	from 22 hp
AT20-150V	153 cm	168 cm	36 cm	165 kg	36	from 24 hp
AT20-170V	170 cm	185 cm	44 cm	175 kg	40	from 28 hp
AT20-185V	186 cm	202 cm	50 cm	186 kg	44	from 35 hp
AT20-200V	203 cm	219 cm	55 cm	199 kg	48	from 40 hp





Technical features

- For carrier vehicles of 12-50 hp
- · Operating width between 85 cm and 200 cm
- · Manual side shift
- KAT.1, KAT.1N rear mounting
- Working depth adjustable up to 11 cm
- · 4 blades per flange optional: 6 blades

AGRITEC specialist dealer

WAM GmbH AGRITEC
Dornierstr. 10 D-68804 Altlußheim
Phone: + 49 (0) 6205 3949 0 fax +49 (0) 6205 3949 49







