



Short description of AT30

The AGRITEC AT30 rotary hoe is a very important and valuable soil cultivation device in the field of gardening and landscaping.

The laterally adjustable rotary hoe of the AT30 series has been specifically developed to be used with municipal and compact tractors of 12–50 hp.

It has rigid and angled cutting blades that are arranged helically around the cutter shaft. This ensures an extremely smooth running with minimal power consumption and produces a clean cut. The cutter shaft is powered by a maintenance-free chain in oil bath. An automatic chain adjuster ensures the optimal positioning of the chain. The rear protective cover and the integrated levelling bar, adjustable via chain, eliminates the bumhp.

Due to its side shifting capacity, the AT30 is also particularly suitable for use in vineyards and orchards. The AT30 rotary hoe has proven its worth in communal establishments and tree nurseries as well.

| Model | Operating width | External width | Side shift | Weight | Blade | Power requirement |
|-----------|--------------------|----------------|------------|--------|-------|----------------------|
| AT30-140V | 140 cm | 165 cm | 15 cm | 270 kg | 24 | 35 – 45 Hp |
| AT30-160V | 160 cm | 185 cm | 20 cm | 290 kg | 28 | 40 – 50Hp |
| AT30-180V | 180 cm | 205 cm | 25 cm | 310 kg | 32 | 45 – 55 Hp |
| AT30-200V | 200 cm | 225 cm | 30 cm | 330 kg | 36 | 50 – 65 Hp |
| AT30-230V | 230 cm | 255 cm | 35 cm | 350 kg | 44 | 55 – 80 Hp |



Technical features

- For carrier vehicles of 35-80 hp
- Operating width between 140 cm and 230 cm
- Manual side shift
- CAT.1, CAT.2 rear mounting
- Working depth adjustable up to 18 cm
- 4 blades per flange optional: 6 blades

AGRITEC specialist dealer



www.AGRITEC.de



Specifications and design are subject to change